

Middle East Research Journal of Engineering and Technology

ISSN: 2789-7737 (Print) ISSN: 2958-2059 (Online) Frequency: Bi-Monthly

DOI: 10.36348/merjet.2024.v04i01.001



Website: http://www.kspublisher.com/ Email: office@kspublisher.com

Faults and Solutions for Smart Traffic Lights

Muhammad Baballe Ahmad^{1*}, Umar Farouk Musa², Yakubu Abdulkareem Ohiani³, Mustapha Babatunde Abimbola⁴ ¹Department of Mechatronics Engineering, Nigerian Defence Academy (N.D.A), Kaduna, Nigeria ²Department of Architectural Technology, School of Environmental Studies Gwarzo, Kano State Polytechnic, Nigeria ³Aircraft Engineering Department, Air Force Institute of Technology, Kaduna, Nigeria ⁴Department of Electrical Engineering, Bayero University, Kano, Nigeria

Abstract: Ambulances, fire departments, and police cars are examples of emergency vehicles (EVs) that greatly benefit communities by saving lives and deterring theft and criminal activity. Automatic control systems are a novel kind of advanced system that function as a driving system using hardware controllers and computers. We require automatic adaptive controllers to manage the traffic light system's open and shut functions since an increase in the number of cars while maintaining the same infrastructure led to a significant traffic issue. In addition to the difficulty emergency vehicles have reaching their location due to traffic congestion caused by heavy cars, traffic problems also include red-light traffic violations, which typically result in accidents on the roadways. Traffic conditions worsen as a result of more cars on the road, making it more difficult to make room for emergency vehicles like ambulances, rescue fire engines, and emergence vehicles. An IoT sensor-based system that detects the arrival of an ambulance at the hotspots using the signals the ambulance sends out can be built to prevent problems waiting for traffic signals in an emergency. The system would then maintain the signals appropriately.

Keywords: Automatic Control, Sensor, Accidents, Traffic Problems, Congestion, Vehicles.

Copyright © 2024 The Author(s): This is an open-access article distributed under the terms of the Creative Commons Attribution 4.0 International License (CC BY-NC 4.0) which permits unrestricted use, distribution, and reproduction in any medium for noncommercial use provided the original author and source are credited.

I. INTRODUCTION

In order to manage conflicting traffic flows, traffic lights—also referred to as traffic lamps or traffic signals—are signaling devices placed at road intersections, pedestrian crossings, and other sites. Due to their inability to adjust to changing road conditions, traditional traffic signal systems, which operate on set cycles, can be a major cause of traffic congestion. Because they make it take longer for people to get where they're going, traffic bottlenecks are bad for both drivers and other road users. Ambulances and police cars are examples of emergency vehicles that could be seriously endangered by this delay. Using dynamic traffic lightswhose functioning changes depending on the traffic conditions at the intersection—is one important way to alleviate traffic congestion at intersections. Since there aren't many scholars in the literature interested in finding solutions to emergency vehicle traffic jam problems, this paper's contribution is the introduction of a revolutionary traffic signal system operation strategy. Two algorithms make up the new strategy: a pure operation mode and a hybrid operation mode. The goal of these operation modes is to shorten the time emergency vehicles must wait at junctions. They make the assumption that an Internet of Things (IoT)-based smart infrastructure system exists that can recognize the arrival of emergency vehicles at a crossroads. The traffic signal operation is changed from fixed cycle mode to dynamic mode by the smart infrastructure system. In order to shorten the time that emergency vehicles must wait at junctions, the dynamic mode controls the traffic signals. The suggested algorithms are simulated in the study, which also emphasizes their benefits. We contrasted our method with the conventional traffic light system and the Wen algorithm found in the literature in order to assess the effectiveness of the new strategy. According to our evaluation study, the suggested algorithms performed better in various traffic circumstances than both the old system and the Wen approach [10]. The traffic light system is controlled by numerous studies. A portion of these techniques included hardware, such as logic circuits and controllers, and were static. These systems don't consider the flow of traffic when opening and closing the traffic light; instead, they rely mostly on a static, continuous time. To forecast the quantity of automobiles or the state of the traffic jam in each direction, several techniques were created [1]. An introduction to the use of fuzzy logic for traffic light control is provided by Study [2]. In this study, the number of automobiles, the length of the queue, and the width of the road are the criteria used by the researchers to manage the cars as a prioritized queue. The green lights that indicated an empty wait were eliminated

Review Paper

*Corresponding Author: Muhammad Baballe Ahmad Department of Mechatronics Engineering, Nigerian Defence Academy (N.D.A), Kaduna, Nigeria

How to cite this paper: Muhammad Baballe Ahmad et al (2024). Faults and Solutions for Smart Traffic Lights. Middle East Res J. Eng. Technol, 4(1): 1-4.

Article History: | Submit: 08.12.2023 | | Accepted: 09.01.2024 | | Published: 13.01.2024 |

during the construction of the fuzzy system. When compared to standard light control systems, the outcome was superior. Researchers discuss the approaches utilized in traffic light system control in-depth in the study [3]. TST and TSC were the primary scopes of many of the searches. While some searches rely on a single parameter, others rely on a set of parameters. The traffic light condition, the length of each light, the required shade of green, the manner in which cars are waiting, the calibration between these cars, and several other significant characteristics are the primary parameters that these systems use. More than 77% of all queries, according to the search, involve the use of simulation tools. Green time, cycle length, phase sequence, change interval, and offset were the primary timing constants. An interview regarding the development of a smart traffic signal system by artificial intelligence is provided in Study [4]. Whether the car weighs more or less than eighty tons is a major factor in this system's operation. This study makes use of Google Earth traffic data; longer travel times are associated with higher traffic intensities. There was an emergency, and cameras were deployed. A software program for modeling logic simulation was used to assess the suggested system. This technology was able to raise the speed of cars to 55% and decrease the number of cars in a given amount of time to 55%. Reducing by 29% the number of automobiles that need to wait and by 38% the amount of time that drivers must wait to cross junctions. Researchers attempt to address the issue of junctions passing on 4-way highways in the study [2]. This study considers vehicle and autonomous vehicle communication in addition to standard characteristics. Sensors, computation, and future car predictions were used to detect cars. According to research, establishing traffic as a network can help reduce traffic issues and provide effective control over traffic signals. Reinforcement training was employed by researchers to manage traffic signals in study [4]. Every study under this scope requires at least two intersections. Natural language processing is used in this study to provide the best answer. This investigation found that more than 160 articles used RL approaches to produce the greatest results. The traffic signal systems were controlled using a variety of techniques, including deep learning and machine learning. The primary benefit of the fuzzy logic approach is its speed in comparison to neural networks, which have a large processing overhead and might not operate instantly. Using historical data, neural networks attempt to forecast the number of automobiles. Although the image processing system can provide real-time data for fuzzy logic to process. The concept made it possible for the system to function in real time, displaying changes in the number of automobiles, the traffic light's response to each variation in the car's number, and the movement of the street directions. Similar to this, the image processing system adds value to the system, particularly in cities with heavy traffic, which can also reduce the likelihood of accidents and delays in time. This system can be designed to treat ambulances as a third fuzzy set, with the requirement that

they open on the street instantly at the top priority, a medium priority with fire engines and police cars, and a lowest priority with other vehicles [5]. Traffic light control systems are used for particular lanes or crossings in metropolitan areas, while fixed cycle traffic lights are usually used to regulate traffic on the roads. Additionally, improper installation can lengthen the time it takes for traffic to clear junctions and result in excessively long wait times for crossing traffic, which can strand emergency vehicles at intersections. By lowering energy consumption and traffic delay, adaptive signal timing management is a technology that can enhance network-wide traffic operations and is more computationally feasible than existing fixed-cycle signal control systems. Despite the existence of specialized adaptive control systems, emergency vehicles cannot be contacted, which is a critical component of smart cities. This issue led to the creation of a unique framework called Emergency Vehicle Adaptive Traffic Lights (EVATL) for smart cities. EVATL combines emergency vehicle communication with an adaptive traffic light mode to improve traffic signal performance and decrease total traffic delay. EVATL uses GPS and the Internet of Things (IoT) to locate emergency vehicles. It interfaces with traffic lights and uses YOLOv8 to operate adaptively based on vehicle density at the traffic signal. Thus, the main objective of the suggested EVATL is to incorporate adaptive traffic signals for smart cities and prioritize an emergency vehicle at the same time. By building several scenarios for an adaptive traffic light and emergency vehicle communication, a graphical user interface (GUI) is created to assess the suggested model. When examining the simulation results of the suggested model EVATL, it is evident that the prompt identification of an emergency vehicle at a predetermined distance significantly reduces the wait time of cars at a traffic signal [6]. This work presents a smart traffic management system that makes use of the Internet of Things (IoT) [17, 22] to help authorities plan more effectively and handle a range of traffic management difficulties. An algorithm is used to efficiently handle various traffic circumstances, and a hybrid strategy—a blend of centralized and decentralized methods—is used to optimize road traffic flow. To do this, the system uses data on traffic density from cameras, sensors, and other devices to modify traffic signals. An alternative artificial intelligence-based technique is used to predict future traffic density in order to lessen traffic congestion. Furthermore, RFIDs [12, 13, 20] are used to prioritize emergency vehicles, such as ambulances and fire brigade vehicles, during a traffic gridlock. This system's component for detecting a fire on the road also includes smoke sensors [19, 21]. To demonstrate the value of the suggested traffic management system, a prototype is developed that not only facilitates better traffic flow but also establishes a connection between neighboring rescue departments via a centralized server. It also gathers useful information that is displayed graphically, which may benefit the government in the future when designing roads [7]. The

population growth and rising car ownership in developing countries like India have led to an increase in traffic congestion and accidents [14-16, 18]. However, a smart traffic control system that uses RFID sensors can lessen these issues by recognizing congested areas and improving traffic flow. This method also enables emergency vehicles to get at their destination more swiftly by granting them priority. The real-time data provided by RFID sensors can also be advantageous to drivers as it can reduce idle time and save them money. Using this information, alternate routes can be suggested to drivers, allowing them to avoid congested areas and reduce the amount of time they spend trapped in traffic. This not only improves traffic flow but also helps reduce pollutants and fuel consumption, making environment cleaner and greener. Emerging countries like India can employ a smart traffic control system with RFID sensors to regulate the increasing traffic flow and reduce traffic accidents. In rising nations like India, an RFID-based smart traffic control system has the potential to greatly enhance the welfare of road users, the economy, and the environment [8]. Using the minimal distance triggering mechanism, the dynamic navigation system and smart traffic light assess the movement of emergency vehicles. In the modern world, traffic congestion is a big problem that causes a lot of chaos and losses to both the economy and people's quality of life. The issues associated with traffic become much more significant when we consider emergency vehicles, including ambulances. In order to reduce travel time, ambulances nowadays frequently drive past intersections carelessly (for example, by speeding past a T junction without considering the risk factors), which raises the possibility that the ambulance will be involved in an accident. The traffic signals in the existing system follow a predefined sequence of green lights; that is, the lights don't turn green until the signal's predetermined timing limit is reached. This system's inability to account for emergency vehicles lowers the system's overall efficiency. Through our project, this static system is altered to become efficient and real-time (i.e., dynamic). First, Proteus DS is used to simulate the primary hardware, which will be a retrofit table system for the existing static time-based traffic system. Second, an Android Studios app is created to control the traffic signal. Thirdly, the desired cloud platform (AWS, Google Cloud, or Microsoft Azure) will be used to construct a web application in [9].

II. FAULTS AND SOLUTIONS FOR SMART TRAFFIC LIGHTS

1. The Intelligent Traffic Signal's Solution The light is dim

Make sure the circuit is functioning properly before turning on the smart traffic light. If it's a new light, measure it with an electric pen or check for voltage in the circuit by installing an incandescent bulb. Once the circuit is verified to be operational, you can begin the subsequent maintenance.

Driver Problems

It is nearly always the driver's fault if the traffic signals are off. Due to their high current and voltage needs, light-emitting diodes (L. E. Ds) cannot be turned on regularly if these parameters are too high or too low. Consequently, it's important to maintain the driver's rectifiers, voltage reducers, constant current drivers, and other components. The driver should be looked at first if, after turning on the light, the lamp beads do not light up. You can buy a new driver to replace the old one at this time.

2. Solutions to the Dimming of the Brightness of Smart Traffic Lights

This problem and the preceding one ought to be fixed together. This could be the situation if the lamp's brightness drops or stays bright.

The Problem of Lamp Beads

Smart traffic light beads are separated into strings. The strings are joined in parallel, and the beads on each strand are connected in series. As a result, the strand of lamp beads will become dark if one of the beads burns out. Every string that has a bead in it will result in the lamp being completely dark. Consideration should be given to the driver's capacitance or resistance if a lamp bead is burned out in each string.

It is evident from their appearance which lamp beads are burned and which are normal. The burned lamp beads have a black dot in the center that cannot be removed. Electric iron can be used to fuse the two welding feet behind the burned lamp beads together if there aren't enough of them. To avoid affecting the lighting's brightness, it is advised to purchase a lamp bead board to replace any burned-out beads.

3. Solution of Smart Traffic Lights Flashing After Turning Off

Verify the wiring issue first if the light flashes after shutting off. The neutral line of the switch control is most likely the issue. Right now, it needs to be fixed quickly to prevent harm. To connect an electric light, the proper method is to flip and manipulate the live and neutral wires.

If there is no problem with the circuit, it is possible that the intelligent traffic light has generated self-inductance current. The easiest way is to buy a 220V relay and connect the coil to the light in series to solve the problem [11].

CONCLUSION

Numerous papers about smart traffic lights have been read for this study, and we have witnessed their effects and technological improvements. There is a discussion of a few issues with smart traffic signals and their fixes.

REFERENCES

- Patel, D., & Rohilla, Y. (2020). Infrared sensor based self-adaptive traffic signal system using arduino board". In 2020 12th International Conference on Computational Intelligence and Communication Networks (CICN) (pp. 175-181) IEEE. doi: 10.1109/cicn49253.2020.9242560
- 2. Jha, M., & Shukla, S. (2014). Design of fuzzy logic traffic controller for isolated intersections with emergency vehicle priority system using matlab simulation. *arXiv* preprint arXiv:1405.0936. https://arxiv.org/ftp/arxiv/papers/1405/1405.0936.pdf.
- Nigam, A., Chaturvedi, M., & Srivastava, S. (2022). An Empirical Study on Parameters Affecting Traffic Stream Variables Under Rainy Conditions. In 2022 14th International Conference on COMmunication Systems & NET work S (COMSNETS) (pp. 818-823). IEEE.
- 4. Komsiyah, S., & Desvania, E. (2021). Traffic Lights Analysis and Simulation Using Fuzzy Inference System of Mamdani on Three-Signaled Intersections. *Procedia computer science*, *179*, 268-280. https://doi.org/10.1016/j.procs.2021.01.006.
- 5. Gdeeb, R. T. (2023). A Controlling Traffic Light system using Fuzzy logic. *Journal of Al-Qadisiyah for computer science and mathematics*, 15(3), 141-153.
- 6. Dodia, A., Kumar, S., Rani, R., Pippal, S. K., & Meduri, P. (2023). EVATL: A novel framework for emergency vehicle communication with adaptive traffic lights for smart cities. *IET Smart Cities*, *5*(4), 254-268. wileyonlinelibrary.com/journal/smc2.
- 7. Reddy, J. D. (2023). AI Based Smart Traffic Management, International Journal of Scientific Research in Engineering and Management (IJSREM), 7(7).
- 8. Adhwanth, D. (2023). Rfid Based Traffic Control System for Emergency Vehicle. *International Journal of Engineering Technology and Management Sciences*, 3(7). DOI:10.46647/ijetms.2023.v07i03.034
- Raghu, N., Phadke, A., Kumar, R., & Joshi, K. (2022). Smart Traffic Light and Dynamic Navigational System for Emergency Vehicles. In Soft Computing for Security Applications: Proceedings of ICSCS 2022 (pp. 391-402). Singapore: Springer Nature Singapore. at: https://www.researchgate.net/publication/364049958.
- Tashtoush, Y., Al-refai, M., Al-refai, G., Darweesh, D. A. K., Zaghal, N., & Darwish, O. (2022). Dynamic Traffic Light System to Reduce the Waiting Time of Emergency Vehicles at Intersections within IoT Environment. International Journal of Computers Communications & Control, 17(3). https://doi.org/10.15837/ijccc.2022.3.4482.
- 11. https://www.trafficsolution.cn/item/three-common-faults-and-solutions-of-smart-traffic-lights.
- 12. Baballe, M. A., & Nababa, F. A. (2021). A comparative study on radio frequency identification system and its various applications. *International Journal of*

- Advances in Applied Sciences (IJAAS), 10(4), 392-398. DOI: 10.11591/ijaas.v10.i4.pp392-398.
- 13. Baballe, M. A. (2021). A Study on the Components used in RFID System and its Challenges. *Global Journal of Research in Engineering & Computer Sciences*, *I*(01), 21-27. Journal homepage: https://girpublication.com/journals/.
- 14. Bari, A. S., Falalu, M. A., Umar, M. A., Sulaiman, Y. Y., Gamble, A. M., & Baballe, M. A. (2022). Accident Detection and Alerting Systems: A Review. Global Journal of Research in Engineering & Computer Sciences, 2(4), 24–29. https://doi.org/10.5281/zenodo.7063008.
- Baballe, M. A., Aminu Ya'u, Ibrahim, S. F., Abdulmuhamin, M., & Mustapha, N. K. (2023). Accident Detection System with GPS, GSM, and Buzzer. Global Journal of Research in Engineering & Computer Sciences, 3(1), 8–14. https://doi.org/10.5281/zenodo.7655016.
- Baballe, M. A., Bari, A. S., Musa, A. L., Mustapha, N. K., Hussain, U. H., Bello, D., & Umar, A. A. (2022). Car Tracking System: Pros and Cons. Global Journal of Research in Humanities & Cultural Studies, 2(5), 188–191. https://doi.org/10.5281/zenodo.7102272.
- 17. Abdulkadir, Z., Ibrahim, A., Muhammad, A., Baballe, M. A., & Sani, S. A. (2023). Contribution of the IoT to the Security System, *Global Journal of Research in Engineering & Computer Sciences*, *3*(4). Journal homepage: https://gjrpublication.com/gjrecs/.
- 18. Abdulrahman Y. A., Bello, M. I., Sani, S. A., Ibrahim, A., & Baballe, M. A. (2023). Fire Extinguisher types and Applications. *Global Journal of Research in Engineering & Computer Sciences*, 3(4), 45–50. https://doi.org/10.5281/zenodo.8286527.
- Amina I., Sadiku A. S., Muntaka D., Abdulmuhaimin M., & M. A. Baballe. (2023). Modern Alarm Sensors for Security Systems. Global Journal of Research in Engineering & Computer Sciences, 3(4), 11–15. https://doi.org/10.5281/zenodo.8193716.
- 20. Ahmad, M. B., & Nababa, F. A. The need of using a Radio Frequency Identification (RFID) System. International Journal of New Computer Architectures and their Applications (IJNCAA) Vol, 11, 22-29.
- 21. Ahmad, M. B., Abdullahi, A. A., Muhammad, A. S., Saleh, Y. B., & Usman, U. B. (2019). The Various Types of sensors used in the Security Alarm system. *International Journal of New Computer Architectures and their Applications* (*IJNCAA*), 9(2), 50-59.
- 22. Çavaş, M., & Ahmad, M. B. (2019). A review advancement of security alarm system using internet of things (IoT). *International Journal of New Computer Architectures and their Applications* (*IJNCAA*), 9(2), 38-49.